

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Currently amended) A disc controller comprising:
a network controlling unit ~~for receiving~~ configured to receive a data input/output request sent from an external device through a network; and
a disc controlling unit formed in the same circuit board in which the network controlling unit is formed, the disc controlling unit coupled to the network controlling unit by an internal bus provided in the circuit board,
wherein the disc controlling unit ~~receives~~ is configured to receive a command sent from the network controlling unit through the internal bus and executes a data input/output for a disc drive in response to the command;
wherein the network controlling unit ~~sends~~ is configured to send the command, for which a plurality of addresses are set, to the disc controlling unit; and
wherein the disc controlling unit ~~receives~~ is configured to receive the command and executes data input/output corresponding to each of the addresses set in the command for the disc drive.
2. (Original) A disc controller according to claim 1, wherein
a file system operates in the network controlling unit,
the data input/output request designates data, which is input/output to/from the disc drive, based on a file name, and
the network controlling unit generates an address corresponding to a storage location of data on the disc drive, which corresponds to the file name set for the data input/output request, and sets the address in the command.

3. (Original) A disc controller according to claim 1,
wherein the address is a logical address for designating a storage location of
data in a logical area organized in a disc space of the disc drive.

4. (Original) A disc controller according to claim 1,
wherein the internal bus is a PCI bus.

5. (Original) A disc controller according to claim 1,
wherein the network controlling unit includes a communicating section
communicating with the external device in accordance with a network protocol.

6. (Currently amended) A disc controller according to claim 1, wherein
a memory accessible in a sharing manner by both the network controlling unit
and the disc controlling unit is formed in the circuit board;

the network controlling unit and the disc controlling unit update, at a
predetermined timing, operation state information indicating each of a plurality of operation
states of the network controlling unit and the disc controlling unit, which is stored in the
memory; and

an occurrence of faults in the network controlling unit and disc controlling unit
is detected based on the operation state information.

7. (Original) A disc controller according to claim 6,
wherein the network controlling unit acquires, from the operation state
information, an operation state of the disc controlling unit which is a sending destination of
the command when the network controlling unit sends the command to the disc controlling
unit, and determines, depending on the acquired operation state, whether the command
should be sent to the disc controlling unit.

8. (Original) A disc controller according to claim 6,
wherein the network controlling unit investigates the operation state of the
disc controlling unit which is a sending destination of the command based on the operation
state information when the network controlling unit can not acquire a receipt notification

concerning the command sent to the disc controlling unit, and determines, depending on a investigation result thereof, whether the command should be sent to the disc controlling unit again.

9. (Original) A disc controlling unit according to claim 6,
wherein the network controlling unit investigates the operation state of the disc controlling unit which is a sending destination of the command based on the operation state information when the network controlling unit can not acquire a receipt notification concerning the command sent to the disc controlling unit, and when the network controlling unit judges that the disc controlling unit is not normally operating, the network controlling unit sends the command to at least one of other disc controlling units.

10. (Original) A disc controller according to claim 6, further comprising:
a user interface for notifying the occurrence of the faults when the occurrence of the faults is detected.

11. (Original) A disc controller according to claim 6,
wherein when the occurrence of the faults is detected, a signal for requesting a restart is sent to one of the network controlling unit and the disc controlling unit where the faults have occurred.

12. (Original) A disc controller according to claim 1, wherein
the disc controlling unit includes an interface for connecting a backup device thereto;

the network controlling unit includes a section for receiving a backup request concerning the data stored in the disc drive from the external device, and for sending a backup command to the disc controlling unit; and

the disc controlling unit includes a section for sending a backup instruction concerning the data stored in the disc drive to the backup device upon receipt of the backup command.

13. (Currently amended) A disc controller comprising:
a network controlling unit ~~for receiving~~ configured to receive a data input/output request sent through a network; and
a disc controlling unit formed in the same circuit board in which the network controlling unit is formed, the disc controlling unit being coupled to the network controlling unit by an internal bus provided in the circuit board, receiving a command sent from the network controlling unit through the internal bus, and inputting/outputting data to/from a disc drive in response to the command,
wherein the plurality of circuit boards connected so as to be capable of communicating with each other are provided;
wherein an occurrence of faults of one of the circuit boards is detected by one of the other circuit boards by exchanging a heartbeat message among the circuit boards; and
wherein when the occurrence of the faults of one circuit board is detected by one of the other circuit boards, the circuit board different from the circuit board causing the faults ~~stands~~ substitutes for a processing of the circuit board causing the faults.
14. (Currently amended) A controlling method of a disc controller having a network controlling unit ~~for receiving~~ configured to receive a data input/output request sent from an external device through a network; and a disc controlling unit formed in the same circuit board in which the network controlling unit is formed, the disc controlling unit being connected to the network controlling unit by an internal bus provided in the circuit board, receiving a command sent from the network controlling unit through the internal bus, and inputting/outputting data to/from a disc drive in response to the command,
the method comprising:
by means of the network controlling unit sending one command, for which a plurality of addresses are set, to the disc controlling unit; and
by means of the disc controlling unit receiving the command and executing data input/output corresponding to each of the addresses set in this command for the disc drive.

15. (Currently amended) A method according to claim 14, wherein the disc controlling unit includes a memory accessible in a sharing manner by both the network controlling unit and the disc controlling unit; the method further comprising:

updating by the network controlling unit and the disc controlling unit ~~update~~, at a predetermined timing, operation state information indicating each of a plurality of operation states of the network controlling unit and the disc controlling unit, which is stored in the memory; and

detecting an occurrence of faults in the network controlling unit and disc controlling unit ~~is detected~~ based on the operation state information.

16. (Currently amended) A method according to claim 14, wherein the disc controlling unit includes an interface for connecting the external device thereto; the method further comprising:

receiving by the network controlling unit ~~receives~~ a backup request concerning data stored in the disc drive from the external device, and ~~sends~~ sending a backup command to the disc controlling unit; and

sending by the disc controlling unit ~~sends~~ the backup command concerning the data of the disc drive to the backup device upon receipt of the backup command.

17. (Currently amended) A method according to claim 14, wherein the disc controlling unit includes the plurality of circuit boards connected so as to be capable of communicating with each other; the method further comprising:

detecting an occurrence of faults of one circuit board ~~is detected~~ by one of the other circuit boards by exchanging a heartbeat message among the circuit boards; and

when one circuit board detects the faults, one of the other circuit boards different from the circuit board causing the faults ~~stands~~ substituting for processing of the circuit board with the faults.

18. (New) A disc controller according to claim 13, further comprising:
a user interface for notifying the occurrence of the faults when the occurrence of the faults is detected.

19. (New) A disc controller according to claim 13,
wherein when the occurrence of the faults is detected, a signal for requesting a restart is sent to one of the network controlling unit and the disc controlling unit where the faults have occurred.

20. (New) A disc controller according to claim 13, wherein
the disc controlling unit includes an interface for connecting a backup device thereto;

the network controlling unit includes a section for receiving a backup request concerning the data stored in the disc drive from the external device, and for sending a backup command to the disc controlling unit; and

the disc controlling unit includes a section for sending a backup instruction concerning the data stored in the disc drive to the backup device upon receipt of the backup command.